

# Tratamiento de Agua

## Depuradores Cronométricos (Equipos Completos)



**V.3749**  
**676 €**

Cabezal AUTOTROL



	<b>V.3743</b>	<b>V.3744</b>	<b>V.3745</b>	<b>V.3746</b>	<b>V.7848</b>
	<b>720 €</b>	<b>794 €</b>	<b>850 €</b>	<b>1.130 €</b>	<b>1.720 €</b>
	<b>5 L</b>	<b>8 L</b>	<b>12 L</b>	<b>26 L</b>	<b>50 L</b>
Ancho (mm)	230	250	285	320	271
Alto (mm)	515	540	650	1120	1300
Profundo (mm)	385	480	425	500	271
Peso (Kg)	11	12	15	32	40
Voltage (V/Hz)	230/50-60	230/50-60	230/50-60	230/50-60	230/50-60
Presión Entrada (bar) (Mín. - Máx.)	2 - 8	2 - 8	2 - 8	2 - 8	2 - 8
Caudal Recomendado (L/H)	800	800	800	--	--
Caudal Máximo (L/H)	1500	1500	1500	1500	1500
Temperatura Ambiente (Mín. - Máx.)	6 - 30	6 - 30	6 - 30	4 - 30	4 - 30
Temperatura Agua (Mín. - Máx.)	8 - 25	8 - 25	8 - 25	4 - 25	4 - 25
Consumo (W)	4	4	4	4	4
Sal Regeneración (Kg)	0,5	1	1,5	2,7	7,2
Máxima Cantidad Sal (Kg)	10	20	25	20	120
Rácor Mezclador	3/4	3/4	3/4	3/4	3/4

### DUREZA DEL AGUA

	20 °f - 11 °d 200 ppm CaCO <sub>3</sub>	30 °f - 16 °d 300 ppm CaCO <sub>3</sub>	40 °f - 22 °d 400 ppm CaCO <sub>3</sub>	50 °f - 28 °d 500 ppm CaCO <sub>3</sub>	60 °f - 33 °d 600 ppm CaCO <sub>3</sub>	Capacidad Ciclo m <sup>3</sup> °F
<b>V.3743</b>	1050	700	525	420	350	21
<b>V.3744</b>	1680	1120	840	672	560	33,5
<b>V.3745</b>	2520	1680	1260	1008	840	50
<b>V.3746</b>	5040	3360	2520	2016	1680	101
<b>V.7848</b>	10500	7000	5250	4200	3500	210